



IMS.LCS.SKJ.0008_Inspection of Hyd Operated Door

Utg. nr. 1 Utarb. av: OOR Dato: 22.02.2018 Godkj. av: MTM Dato: 22.02.2018 Rev. av: Dato:

CUSTOMER REF.		TESTED BY:	
PROJECT REF.		DATE TESTED:	

V=OK X=DEFECT

	Door Number					
ITEM	Direction L/R					
1	Rubber gasket condition					
2	Dia - Wheel Bottom Front/Rear cond:					
	dia:	/ mm	/ mm	/ mm	/ mm	/ mm
3	Dia - Wheel top. Front/Rear cond:					
	dia:	/ mm	/ mm	/ mm	/ mm	/ mm
4	Springs door open / close					
5	Cam/axel for operating handle					
6	Mechanical locking					
7	Closing time					
8	Piston rod/packing box					
9	Manometer					
10	Accumulator	bar	bar	bar	bar	bar
11	HPU - Pressure start:	bar	bar	bar	bar	bar
	stop:	bar	bar	bar	bar	bar
12	3 stroke test					
13	Oil level					
14	Oil level switch					
15	Hand pump cond:					
	time:	sec.	sec.	sec.	sec.	sec.
16	JB Boxes					
17	Alarm Bell					
18	Yellow blink lamp (if fitted)					
19	Red blink lamp					
20	Proximity switches					
21	Emerg. station - hand generator cond:					
	time:	sec.	sec.	sec.	sec.	sec.
22	Control cabinet					
23	Control card cond:					
	hrs:					
24	Remote closing from bridge	sec.	sec.	sec.	sec.	sec.



IMS.LCS.SKJ.0008_Inspection of Hyd Operated Door

Utg. nr.	Utarb. av:	Dato:	Godkj. av:	Dato:	Rev. av:	Dato:
1	OOR	22.02.2018	MTM	22.02.2018		

COMMENTS: